

CRI>90 COB LED STRIP




Abmessungen/Dimensions	5000mm
Leuchtmittel/Light source	COB
Lichtstrom /Luminous Flux	150 – 1800lm/m
Leistung/Wattage	10 –18W/m
Anzahl LEDs/LED Qty	528LED/m
IP-Schutzart/IP-Protection	IP20, IP67
Schutzklasse/Protection Class	III




Beam angle 170°

528LED/m



528LED/m



Artikelnummer Article Number	IP IP	LEDs/m LEDs/m	CRI CRI	Teilungsmaß Cutting unit	Leistung Wattage	PCB Breite PCB Width	Farbe Color	Lichtstrom Luminous Flux
Constant Voltage Strips								
P2408Y528K-27	IP20	528LED/m	CRI>90	45.45mm	14W/m	8mm	2700K	1300lm/m
P2408Y528K-30	IP20	528LED/m	CRI>90	45.45mm	14W/m	8mm	3000K	1350lm/m
P2408Y528K-40	IP20	528LED/m	CRI>90	45.45mm	14W/m	8mm	4000K	1400lm/m
P2408Y528K-65	IP20	528LED/m	CRI>90	45.45mm	14W/m	8mm	6500K	1450lm/m
P2408Z528K-27	IP67	528LED/m	CRI>90	45.45mm	14W/m	10mm	2700K	1250lm/m
P2408Z528K-30	IP67	528LED/m	CRI>90	45.45mm	14W/m	10mm	3000K	1300lm/m
P2408Z528K-40	IP67	528LED/m	CRI>90	45.45mm	14W/m	10mm	4000K	1350lm/m
P2408Z528K-65	IP67	528LED/m	CRI>90	45.45mm	14W/m	10mm	6500K	1400lm/m
P2408Y528K-R	IP20	528LED/m	-	45.45mm	14W/m	8mm	Red	160lm/m
P2408Y528K-Y	IP20	528LED/m	-	45.45mm	14W/m	8mm	Yellow	1000lm/m
P2408Y528K-B	IP20	528LED/m	-	45.45mm	14W/m	8mm	Blue	160lm/m
P2408Y528K-G	IP20	528LED/m	-	45.45mm	14W/m	8mm	Green	980lm/m
P2408Z528K-R	IP67	528LED/m	-	45.45mm	14W/m	10mm	Red	150lm/m
P2408Z528K-Y	IP67	528LED/m	-	45.45mm	14W/m	10mm	Yellow	980lm/m
P2408Z528K-B	IP67	528LED/m	-	45.45mm	14W/m	10mm	Blue	150lm/m
P2408Z528K-G	IP67	528LED/m	-	45.45mm	14W/m	10mm	Green	960lm/m
P2410Y528K-22	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	2200K	1400lm/m
P2410Y528K-27	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	2700K	1450lm/m
P2410Y528K-30	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	3000K	1500lm/m
P2410Y528K-35	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	3500K	1600lm/m
P2410Y528K-40	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	4000K	1700lm/m
P2410Y528K-50	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	5000K	1750lm/m
P2410Y528K-65	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	6500K	1800lm/m


CRI>90 COB LED STRIP

Artikelnummer Article Number	IP IP	LEDs/m LEDs/m	CRI CRI	Teilungsmaß Cutting unit	Leistung Wattage	PCB Breite PCB Width	Farbe Color	Lichtstrom Luminous Flux
P2410Z528K-22	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	2200K	1350lm/m
P2410Z528K-27	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	2700K	1400lm/m
P2410Z528K-30	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	3000K	1450lm/m
P2410Z528K-35	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	3500K	1550lm/m
P2410Z528K-40	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	4000K	1650lm/m
P2410Z528K-50	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	5000K	1700lm/m
P2410Z528K-65	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	6500K	1750lm/m


MIT BEGRENZUNGSWAND UM DIE COB / WITH BOUNDING WALL AROUND THE COB

Beam angle 120°

528LED/m



528LED/m



Artikelnummer Article Number	IP IP	LEDs/m LEDs/m	CRI CRI	Teilungsmaß Cutting unit	Leistung Wattage	PCB Breite PCB Width	Farbe Color	Lichtstrom Luminous Flux
Constant Voltage Strips								
P2408Y528BK-27	IP20	528LED/m	CRI>90	45.45mm	14W/m	8mm	2700K	1300lm/m
P2408Y528BK-30	IP20	528LED/m	CRI>90	45.45mm	14W/m	8mm	3000K	1350lm/m
P2408Y528BK-40	IP20	528LED/m	CRI>90	45.45mm	14W/m	8mm	4000K	1400lm/m
P2408Y528BK-65	IP20	528LED/m	CRI>90	45.45mm	14W/m	8mm	6500K	1450lm/m
P2408Z528BK-27	IP67	528LED/m	CRI>90	45.45mm	14W/m	10mm	2700K	1250lm/m
P2408Z528BK-30	IP67	528LED/m	CRI>90	45.45mm	14W/m	10mm	3000K	1300lm/m
P2408Z528BK-40	IP67	528LED/m	CRI>90	45.45mm	14W/m	10mm	4000K	1350lm/m
P2408Z528BK-65	IP67	528LED/m	CRI>90	45.45mm	14W/m	10mm	6500K	1400lm/m
P2410Y528BK-22	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	2200K	1400lm/m
P2410Y528BK-27	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	2700K	1450lm/m
P2410Y528BK-30	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	3000K	1500lm/m
P2410Y528BK-35	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	3500K	1600lm/m
P2410Y528BK-40	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	4000K	1700lm/m
P2410Y528BK-50	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	5000K	1750lm/m
P2410Y528BK-65	IP20	528LED/m	CRI>90	38.46mm	18W/m	10mm	6500K	1800lm/m
P2410Z528BK-22	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	2200K	1350lm/m
P2410Z528BK-27	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	2700K	1400lm/m
P2410Z528BK-30	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	3000K	1450lm/m
P2410Z528BK-35	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	3500K	1550lm/m
P2410Z528BK-40	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	4000K	1650lm/m
P2410Z528BK-50	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	5000K	1700lm/m
P2410Z528BK-65	IP67	528LED/m	CRI>90	38.46mm	18W/m	12mm	6500K	1750lm/m