




ROUND A

Mounted luminaire

Ceiling-mounted luminaire with mid-power LEDs optimized for a flat and glare-free illumination as general lighting.

Lamp & Lumen Output	At Ø 240mm (Mid-Power LED, 8W, 450mA, 1500lm)
	At Ø 340mm (Mid-Power LED, 14W, 450mA, 1950lm)
	At Ø 440mm (Mid-Power LED, 18,3W, 450mA, 2740lm)
	At Ø 640mm (Mid-Power LED, 32,8W, 450mA, 4240lm)
	At Ø 940mm (Mid-Power LED, 76,8W, 450mA, 9880lm)
Reflector	Diffuse plastic disc
Control gear	LED driver internal
Dimming (options)	1-10V, DALI, Push
Luminaire type, mounting	Mounted
Dimensions	DxH (240-940mm)x120 mm
Cast, heat sink	Steelsheet
Colour/finish	Powder coated, RAL 9016 (other RAL colours optional)
Protection marking, compliance	IP20, CE
Specials	Customized versions, more light colours or colour renderings on request



Article number: _ _ _ _ _

Luminaire type	Identification	Reflector / Beam angle	Color temperature	CRI	Driver	RAL
I = Mounted	3040 = ø240	Z = Diffuse	30 = 3000 K	80	EV = On/Off	0000 = None
	3041 = ø340		40 = 4000 K	90	AV = 1-10V	1000 - 9018 = RAL
	3042 = ø440				DA = Dali	
	3043 = ø640				PH = Push	
	3044 = ø940					