




Mini Line T

Surface mounted

Diffused and casted for an optimal and homogeneous appearance.






Lamp	LED flex strips 14,4W / m
lighting technology	Diffused and casted
Electrical design	LED Treiber external
Dimming	1-10V, DALI, Push
Light type	surface mounted
Dimension	18,4 x 25 (W x H)
Casing	Aluminiumprofile
Protection class, marking	IP68, CE
Specials	Special version or additional light colors / CRI optional



Article number: _ _ _ _ _

Luminaire type	Identification	Reflector / Beam angle	Color temperature	CRI	Driver	RAL
I = surface mounted	9804	Z = Diffus	30 = 3000 K	80	EV = On/Off	0000 = None
			40 = 4000 K	90	DA = Dali	
			50 = 5000 K		PH = Push	
			01 = RGBW			
			02 = RGB			

Extras:

Beschreibung	Artikel-Nr.	
1x mounting bracket with tension spring	1012	
2x retaining clips, incl. Screws, V2A stainless steel	1013	
Retaining clip set incl. 2 mounting clips and 2 screws, V2A stainless steel, high holding power	1014	
1x end cap T-profile high version made of aluminum, incl. 4 screws, thickness (including wings): 10mm	1015	
1x End cap T-profile short version made of aluminum, for subsequent mounting of the retaining springs, incl. 4 screws, thickness (including wing): 10mm	1016	
1x end cap T-profile short version made of aluminum with 8,5mm bore, for subsequent mounting of the retaining springs, incl. 4 screws, thickness (including wing): 10mm	1017	